

## ***Lifesmart Spa Specifications***

<b>Spa Model (Seating)</b>	<b>Footprint Dimension</b>	<b>Height</b>	<b>Effective Filter Area</b>	<b>Heater (Watts)</b>	<b>Water Capacity</b>	<b>Dry Weight</b>	<b>Filled Weight</b>	<b>Electrical Requirements</b>
<b>LS100/DX (4 person)</b>	5'10" x 5'1"	32"	50 SQFT	Heat Recovery	205 gal	270 lbs.	2,698 lbs.	110 V, 15-amp GFCI protected circuit
<b>LS200/DX (4 person)</b>	6'5" x 5'6"	29"	25 SQFT	Heat Recovery	220 gal	244 lbs.	2,799 lbs.	110 V, 15-amp GFCI protected circuit
<b>LS350DX/PLUS (5 person)</b>	6' x 6'9"	34"	50 SQFT	Heat Recovery	315 gal	351 lbs.	3,881 lbs.	110 V, 15-amp GFCI protected circuit
<b>LS450DX (6 person)</b>	6'9" x 6'9"	34"	50 SQFT	Heat Recovery	270 gal	440 lbs.	3,766 lbs.	110 V, 15-amp GFCI protected circuit
<b>LS500 PLUS (5 person)</b>	7'3" x 6'5"	34"	50 SQFT	Heat Recovery	290 gal	423 lbs.	3,743 lbs.	110 V, 15-amp GFCI protected circuit
<b>LS550 PLUS (5 person)</b>	7'3" x 6'5"	34"	50 SQFT	4,000	290 gal	445 lbs.	3,765 lbs.	230 V, 50-amp GFCI protected circuit
<b>LS600DX (7 person)</b>	6'9" x 6'9"	34"	50 SQFT	4,000	290 gal	478 lbs.	4,148 lbs.	230 V, 50-amp GFCI protected circuit
<b>LS700DX (7 person)</b>	6'9" x 6'9"	34"	50 SQFT	4,000	285 gal	583 lbs.	4,210 lbs.	230 V, 50-amp GFCI protected circuit
<b>SERENO (4 person)</b>	6'3" x 6'3"	34"	50 SQFT	1,000 or 4,000	245 gal	406 lbs.	3,171 lbs.	110 V, 15 amp or 230 V, 50-amp GFCI protected circuit
<b>TIERRA (5 person)</b>	7'3" x 6'5"	34"	50 SQFT	4,000	327 gal	426 lbs.	4,058 lbs.	230 V, 50-amp GFCI protected circuit
<b>LEGANZA (6 person)</b>	7'3" x 6'5"	34"	50 SQFT	4,000	290 gal	445 lbs.	3,765 lbs.	230 V, 50-amp GFCI protected circuit
<b>ESTRELLA L (6 person)</b>	7'0" x 7'0"	36"	50 SQFT	4,000	330 gal	796 lbs.	4,737 lbs.	230 V, 50-amp GFCI protected circuit
<b>ESTRELLA NL (7 person)</b>	7'0" x 7'0"	36"	50 SQFT	4,000	360 gal	700 lbs.	4,960	230 V, 50-amp GFCI protected circuit
<b>PLAYA (3 person)</b>	7'0" x 5'5"	29.5"	35 SQFT	4,000	210 gal	663 lbs.	2,958 lbs.	230 V, 50-amp GFCI protected circuit
<b>CARINO (6 person)</b>	7'5" x 7'5"	36"	50 SQFT	4,000	409 gal	893 lbs.	5,433 lbs.	230 V, 50-amp GFCI protected circuit